

SEMI-SLICK TIRE TEMPESTA P1

FEATURES AND BENEFITS

TIME TRIAL PACE: A+



TREAD DEPTH SENSITIVITY: A



HEAT TOLERANCE: A-



WARMUP: B



WEAR: A-



WET PERFORMANCE: B-



SPORT CAR TIRE

SPEED

W / Y XL / W XL

15 INCHES

16 INCHES

17 INCHES

18 INCHES

19 INCHES

20 INCHES

21 INCHES

- SAFE
- SAVE FUEL
- BRAKE
- CONTROL

Tread design

The TEMPESTA P1 is for drivers who know what it means to really push a car. Its optimized construction and tread design



Balances dry performance

keeping you fully under control in extreme driving situations.

wet traction

keeping you fully under control in extreme driving situations.

TEMPESTA P1

UTQG	TREADWEAR	TRACTION	TEMPERATURE
	200/260	AA	A

Series	SIZES	L.I./S.R.	TREAD DEPTH(MM)	STANDARD RIM	OVERALL DIAMETER(MM)	MAX LOAD		MAX PRESSURE	
						KG	LBS	KPA	PSI
25	295/25R19	94W XL	5.6	101/2J	631	670	1477	340	50
	345/25R19	99W/Y	5.6	121/2J	660	690	1521	300	44
	285/30R15	88W	5.6	10J	551	560	1234	300	44
	305/30R15	92W	5.6	11J	572	630	1388	300	44
30	285/30R17	95W XL	5.6	10J	572	690	1521	340	50
	295/30R18	98W XL	5.6	101/2J	635	750	1653	340	50
	315/30R18	98W	5.6	11J	647	750	1653	300	44
	345/30R18	107W XL	5.6	12J	665	975	2149	340	50
	315/30R21	105Y XL	5.6	11J	723	925	2039	340	50
	245/35R15	84W	5.6	81/2J	553	500	1102	300	44
35	255/35R18	94Y XL	5.6	9J	635	670	1477	340	50
	265/35R18	97W XL	5.6	91/2J	643	730	1609	340	50
	235/35R19	96Y XL	5.6	9J	661	710	1565	340	50
	245/35R19	93W/Y XL	5.6	81/2J	655	650	1432	340	50
	255/35R19	96W/Y XL	5.6	9J	661	710	1565	340	50
	265/35R19	98W/Y XL	5.6	91/2J	669	750	1653	340	50
	275/35R19	100W/Y XL	5.6	91/2J	675	800	1763	340	50
	255/35R20	97Y XL	5.6	9J	686	730	1609	340	50
40	225/40R15	83W	5.6	8J	558	487	1074	300	44
	245/40R17	95W XL	5.6	81/2J	628	690	1521	340	50
	225/40R18	92W XL	5.6	8J	637	630	1388	340	50
	235/40R18	95W XL	5.6	81/2J	645	690	1521	340	50
45	245/40R18	97Y XL	5.6	81/2J	653	730	1609	340	50
	225/45R17	94Y XL	5.6	71/2J	634	670	1477	340	50
	195/50R15	82W	5.6	6J	577	475	1047	300	44
55	195/55R15	85W	5.6	6J	595	515	1135	300	44

TEMPESTA P1+

UTQG	TREADWEAR	TRACTION	TEMPERATURE
	200/260	AA	A

Series	SIZES	L.I./S.R.	TREAD DEPTH(MM)	STANDARD RIM	OVERALL DIAMETER(MM)	MAX LOAD		MAX PRESSURE	
						KG	LBS	KPA	PSI
25	295/25R21	96Y XL	5.6	10 1/2J	681	710	1565	340	50
	345/25R21	104W XL	5.6	-	-	-	-	-	-
	255/30R19	91Y XL	5.6	9J	637	615	1355	340	50
	305/30R19	102Y XL	5.6	11J	667	850	1873	340	50
30	295/30R19	100Y XL	5.6	10 1/2J	661	800	1763	340	50
	245/30R20	90Y XL	5.6	8 1/2J	656	600	1322	340	50
	285/30R20	99Y XL	5.6	10J	680	775	1708	340	50
	305/30R20	103Y XL	5.6	11J	692	875	1929	340	50
	315/30R20	104Y XL	5.6	11J	698	900	1984	340	50
	325/30R20	106Y XL	5.6	11 1/2J	704	950	2094	340	50
	325/30R21	108Y XL	5.6	11 1/2J	729	1000	2204	340	50
	245/35R18	92Y XL	5.6	8 1/2J	629	630	1388	340	50
35	275/35R18	99Y XL	5.6	9 1/2J	649	775	1708	340	50
	285/35R19	103Y XL	5.6	10J	683	875	1929	340	50
	235/35R20	92Y XL	5.6	8 1/2J	672	630	1388	340	50
	245/35R20	95Y XL	5.6	8 1/2J	680	690	1521	340	50
	265/35R20	99Y XL	5.6	9 1/2J	694	775	1708	340	50
	285/35R20	104Y XL	5.6	10J	708	900	1984	340	50
	295/35R20	105Y XL	5.6	10 1/2J	714	925	2039	340	50
	235/40R17	94Y XL	5.6	8 1/2J	620	670	1477	340	50
40	215/40R18	89Y XL	5.6	7 1/2J	629	580	1278	340	50
	265/40R18	101Y XL	5.6	9 1/2J	669	825	1818	340	50
	235/40R19	96Y XL	5.6	8 1/2J	671	710	1565	340	50
	245/40R19	98Y XL	5.6	8 1/2J	679	750	1653	340	50
45	255/40R17	98W XL	5.6	-	-	-	-	-	-
	205/45R16	87W XL	5.6	7J	590	545	1201	340	50
	205/45R17	88Y XL	5.6	7J	616	560	1234	340	50
	215/45R17	91Y XL	5.6	7J	626	615	1355	340	50
	235/45R17	97Y XL	5.6	8J	644	730	1609	340	50
50	205/50R15	89W XL	5.6	6 1/2J	587	580	1278	340	50
55	205/55R16	94W XL	5.6	6 1/2J	632	670	1477	340	50